



DIMENSIONS		
length	500 mm	19.7"
width	400 mm	15.7"
height	150 mm	6"
internal length	432 mm	17"
internal width	257 mm	10"
internal depth	113mm	4.5"
wall thickness	28mm	1.1"
weight	7 kg	15.4 lbs
crated weight	20.25 kg	44.5 lbs
crated size	60x50x28cm	24x20x11"

GEO BASINS CAN BE MADE TO INDIVIDUAL SIZES.....
PLEASE CONTACT US TO DISCUSS YOUR REQUIREMENTS

CONSTRUCTION

The Geo Basin is constructed from a laminated teak composite. It is fixed to the wall by means of metal cantilever brackets and a timber wall plate as illustrated. For a secure and level installation, the wall itself should be flat, vertical and have either a solid timber or masonry structure to take screw fixings. The bottom of the basin is shaped to ensure even drainage.

PLUMBING CONNECTIONS

Geo Basins are fitted with a standard 1 1/4" chrome Presflo(chainless) waste compatible with standard basin traps. The waste is fitted in the center of the basin. Generally, taps are wall mounted but there is sufficient depth at the back of the basin for some conventional tap styles.

Overflows are *not* fitted as a standard item.

CARE & MAINTENANCE

All Geo Basins are finished with a specially formulated marine polish. It has exceptional adhesion to the timber, forming a tough layer which will not absorb stains and which is easy to clean using ordinary non-abrasive bathroom and kitchen cleaners. Products containing bleach should be avoided as they may lighten the timber unevenly. However, limescale removers can be used without the risk of damage.